

Montgomery County Fair Association Truck Pull Rules

Light Duty Factory Stock Gas (½ ton, 5 or 6 lug)

1. 26-in. Hitch height with clevis
2. No added weight
3. No blocked rear ends, no traction bars
4. Drive shaft loops front and back (chain or cable) mandatory
5. Factory stock means just how you bought it from the dealer showroom
6. JUDGES HAVE FINAL SAY!

Heavy Duty Factory Stock Gas (¾ ton to 1 ton, 6,500 lbs. max.)

7. 26-in. Hitch height with clevis
8. No added weight
9. No blocked rear ends, no traction bars
10. Drive shaft loops front and back (chain or cable) mandatory
11. Factory stock means just how you bought it from the dealer showroom
12. JUDGES HAVE FINAL SAY!

Street Stock—6,000 lbs. and 6,500 lbs.

13. Mild cam allowed and aluminum intake
14. Can have headers
15. Stock ignition
16. No front weight bracket longer than 6-inches from factory front bumper
17. 93 octane fuel, no race fuel
18. Drive shaft loops front and back (chain or cable) mandatory
19. 26-inch hitch height with clevis
20. No cut tires
21. May block rear end, blocks must be removable
22. Traction bars allowed (safety measure)
23. JUDGES HAVE FINAL SAY!

Street Stock Diesel—8,500 lbs.

24. No cut tires
25. No front weights or weight bracket—weights must be in bed of truck
26. May block rear end and traction bars allowed
27. 26-inch hitch height with clevis
28. No boosting
29. Duals allowed
30. No more modifications than chip, exhaust, intake
31. JUDGES HAVE FINAL SAY!

8,500 lbs. Modified Diesel Trucks

32. No sanctioned trucks
33. 35-inch DOT tires max; no cut tires
34. Front weight bracket allowed, 60-inch limit
35. May block rear end; must have rear springs
36. Traction bars allowed
37. 26-inch hitch height with clevis
38. Boosting allowed
39. Duals allowed
40. Drive shaft shields required
41. Must have OEM motor
42. Water injection only
43. JUDGES HAVE FINAL SAY!

Modified Trucks—6,000 lbs. and 6,500 lbs.

44. Front weight bracket allowed, 60-inch limit
45. May block rear end, blocks must be removable
46. 26-inch hitch height with clevis
47. 33/1250 DOT tires; not cut tires
48. Open headers allowed, no aluminum heads
49. Blow proof clutch housing or blanket
50. No alcohol or nitrous
51. Natural aspirated motor
52. One-ton maximum drive train
53. 540 cubic inch max.
54. Drive shaft shields required
55. Any wheel base over 140 inches must drop 500 lbs.
56. JUDGES HAVE FINAL SAY!

For more information, contact:

Don Walker (217) 532-2441—tractors
Dan Eichkoff (217) 532-9348—tractors
Justin Brown (217) 556-9510—diesel trucks
Ryan Brown (217) 827-2216—diesel trucks
Jeremy Cray (217) 341-2568—trucks